PRODUCT SPECIFICATION Touch Sensor Hardware

.posts and brackets for fitting Touch Sensors..



INTERNAL POST

High quality post for use with the Oval (OASS etc.) range of Touch Sensors.

50mm powder coated mild steel tube (seamless) with heavy duty 15mm x 150mm diameter mild steel base.

> POSTC (CREAM FINISH) DIMENSIONS (mm) 900mm (h)x150mm (base)x 50mm (tube) + Oval Sensor

EXTERNAL POST

High quality 6" stainless steel tube complete with Round Touch Sensor.

Includes heavy duty 15mm x 150mm diameter mild steel base.



POSTEXT (STAINLESS) DIMENSIONS (mm) 900mm(h) x 152.4 (dia) + Round Sensor

ECOPOST - INTERNAL / EXTERNAL POST

Internal / external post for mounting the Architrave range of Touch Sensors. This is our best selling post combining flexibility and great value for money. 50mm box section steel available powder coated in black or silver. Complete base / cover plate with pre-drilled holes and all fixings to fix Touch Sensor.



ECOPOST-BLK (BLACK) & ECOPOST-SIL (SILVER)

DIMENSIONS (mm) POST: 1040mm (h) x 150mm sq. (base) x 52mm (tube) STAINLESS STEEL BASE / COVER PLATE : 158mm sq. x 40mm (h)

+ ARC / TXARC Touch Sensor



John Wainwright Systems Ltd. | Westfield Court | 3rd Avenue | Westfield Industrial Estate | Radstock | BA3 4XD | UK T +44 (0)1761 414700 F +44 (0)1761 414722 W www.jwsltd.co.uk E post@jwsltd.co.uk