DIGIWAY PLUS Door automation (EN16005 compliant)

Range: DIGIWAY

The new DIGIWAY PLUS offers a high quality, high performance product to automate single and double swing-doors.

Using the experience gained in manufacturing the original DIGIWAY, the new DIGIWAY PLUS has many features which will enhance the whole experience of automating swing-doors - from the LCD display to step-through installation and set up, to the integral pad to programme the parameters (this can also be completed via a hand-held transmitter.

A new encoder lets DIGIWAY PLUS know the exact position of the door at all times which eliminates the requirement for a door stop. Double doors can be simply managed as being master/slave configuration, which will also control rebated doors.

As well as the simplicity to install and the high performance of DIGIWAY PLUS, there are numerous features which increases the flexibility of the product and makes it suitable for many applications. These include:

- Push & Go / Pull & Go
- Fire alarm input
- Night / Day mode
- Free open, auto-close
- Speed, torque & velocity adjustment
- Disabled entry mode
- Electrolock pause timer
- PIR/Radar "masking"
- Wind-stop torque adjustment
- Obstacle management

Technical specification

Overall dimensions Power supply	511 x 90 x 110mm 230Vac - 50Hz
Motor power	33W
Motor voltage	24Vdc
Battery	12Vdc, 1.3AH
Weight	5Kg
IP rating	IP22
Operating temperature	-10 to +55°C
Mains fail operation	4 hours



Please contact CDVI for advice about EN16005 and any risk assessment that may be required on site.

- Easy install & set up
- Complies to EN16005
- LCD display
- Programming via internal buttons or transmitter
- Inward or outward opening
- DDA
- Standby battery included
- 2-year warranty

Product codes

DWPS102U	Digiway Plus with universal arm
DWSE	55mm extension shaft
DWPCS	Interconnecting cable (double door)
DMSP-KS	3-position keyswitch



cdvi.co.uk cdvigroup.com