Digiway SRSpring Return



The long awaited Digiway Spring Return offers high quality and high performance, assisted by a chain driven spring mechanism it is ideally suited for heavy manual environments and offers full assisted door automation when required.

An evolution to Digiway Plus, the Digiway Plus is able to automate doors up to 180Kg and 1.4m wide combined with easy set up and control with forward thinking features. Keeping the setup process near identical to Digiway Plus the Digiway Spring Return offers installers a familiar set-up process to make installation quick and simple.

Setup is carried out using the inbuilt LCD and programming buttons or via the RF remote control making installation easy and hassle free. Operation is reliable, smooth and quiet thanks to the chain drive and integrated shaft encoder continually checking the status of the door being automated ensuring full compliance with EN16005.

Technical Specifications

Usage: See graph Figure.1

Overall Dimensions: 685 x 110 x 90mm

Operating temperature: -10°C to +55°C

Power supply: 230 Vac - 50 Hz

Power for auxiliary devices:

12 Vdc / 500 mA (max)

Power for electrolock:

• 12 Vdc / 1A (max) or 24Vdc / 0.5A


Max power: 100 W

Weight: 10.5kg

Transmitters encoding: Keeloq® Hopping Code

Transmitter memory: 50 transmitters





Key Features

- Heavy Duty Operation
- Semi-Automatic (Spring Return) & Fully
 Automatic (Motor Return)
- Universal Arm Included
- Slim Line Profile
- Built in Programmer & Receiver
- Quiet operation
- Conforms to EN16005

