



JWS RECOMMEND
INTERNET EXPLORER



YOUR ACCESS CONTROL YOUR CHOICE OF DEVICE

JWSLRPROX - UP TO 800mm PROXIMITY READER FOR ACCESS CONTROL & DISABLED ACCESS



Technical Specification

- Card Type: EM-ID Mid-distance Card
- Reading Range: Up to 800mm*
- Output Format: Wiegand 26/34
- Voltage: DC12v
- Current: ≤100mA
- Working Temperature: -10-70 degree
- Color: Dark Grey
- Dimensions: 260x260x35mm
- Working Humidity: 10%-90%
- IP 65 - Suitable for outside use
- Replaces JWSPROX60
- For Entry or Exit only (i.e. not two readers per door)

Please note the following to help optimise reading distance*
Do not mount on or near to metallic objects.
Cards and Reader must be in the same plane: i.e. flat upright card facing reader
Readers must not be within 5m of each other (you may experiment on site to optimise proximity)

Reader	Navigator IP Reader Terminal Block
Black	0v
Red	+12v
Green	Clock
White	Data

*Read range is optimised using JWS Long Range Hard Shell Cards only, fobs and other cards will be considerably less.

NAVIGATOR IP



Install Standalone or Networked
up to 200 doors with 10,000 users.

Navigator IP is a true two door Access Control Unit (Entry & Exit Readers on both doors) supplied boxed with 12v DC 2.5A lock PSU.

It's Browser-based with in built Web Server (not cloud), and easy to setup with no software installation or internet connection required.

